



**Your search is over.** The VR8215 Direct Ignition Gas Valves replace nearly all standard and slow-opening VR8205 and VR8215 controls. The VR8215 valve can be mounted in any orientation and the reduced installation turning radius makes it much easier to install. With the quiet operation, smaller size and ease of installation, the VR8215 gas valve is a great fit for tight and open applications.

# Spend less time searching for the right part.

Combined, the VR8215S and VR8215T valves replace over 61 OEM and White Rodgers controls.

## Growing opportunity.

With a large install base, many manufacturers used VR8205 and VR8215 valves in their direct ignition, gas appliances. This presents a growing replacement opportunity as they come out of warranty. These valves allow you to capture that replacement business and grow your revenues.

## Compact design.

The VR8215 gas valves have a very compact design and a 2.3" swing radius. This gives you much more room to work in tight spaces.

## Multipoise mounting.

Multipoise mounting enables you to install the VR8215 at any angle.

## Learn More

For more information about Honeywell gas valves, contact your Honeywell distributor, call **1-800-345-6770**, ext. 423 or visit [customer.honeywell.com](http://customer.honeywell.com)

## Automation and Control Solutions

In the US:

Honeywell

1985 Douglas Drive North

Golden Valley, MN 55422-3992

In Canada:

Honeywell Limited

705 Montrichard

Saint-Jean-sur-Richelieu, Quebec

J2X 5K8

[www.honeywell.com](http://www.honeywell.com)



## Cross Reference Guide

<b>VR8215S1503</b>	Standard opening characteristic Temperature: -40° to 175° F (-40° to 79° C)		
<b>Honeywell</b>			
VR8205S2262,	VR8205S2270,	VR8205S2296,	VR8205S2338,
VR8205S2353,	VR8205S2361,	VR8205S2379,	VR8205S2395,
VR8205S2437,	VR8205S2858,	VR8205S2882,	VR8205S5802,
VR8205S5828,	VR8205S5836,	VR8205S5844,	VR8215S1222,
VR8215S1263,	VR8215S5207,	VR8215S5215,	VR8205A2008,
VR8205A2016,	VR8205A2024,	VR8205A2065,	VR8205A2081,
VR8205A2131,	VR8205A2263,	VR8205A2800,	VR8205M1080,
VR8205M1106,	VR8205M1122,	VR8205M1130,	VR8205M1148,
VR8205M1155,	VR8205M1163,	VR8205M2310,	VR8205M2401,
VR8205M2476,	VR8205M2484,	VR8205M2831,	VR8205M2864,
VR8205M2872,	VR8205M2880,	VR8205M5024,	VR8205M5032
<b>White Rodgers</b>			
36G22-214, 36J22-214, 36G22-207			
<b>VR8215T1502</b>	Slow opening characteristic Temperature: -40° to 175° F (-40° to 79° C)		
<b>Honeywell</b>			
VR8205H1003,	VR8205H1011,	VR8205H2605,	VR8205H2621,
VR8205K1157,	VR8205K1173,	VR8205K2247,	VR8205K2593,
VR8205K2619,	VR8205T5801,	VR8215T1205,	VR8215T1239,
VR8215T5206,	VR8215T5214		

Follow us on Twitter:

@honeywellcpro



YouTube:

@honeywellcpro



# Honeywell