


# BLUE MONSTER<sup>®</sup>

Products




**MILL-ROSE** *Clean-Fit Products*

[bluemonsterproducts.com](http://bluemonsterproducts.com)



# MILL-ROSE

## BLUE MONSTER Products



### Blue Monster® PTFE Thread Seal Tape - Mini-Monster Contractor Grade

*Rugged, general purpose tape in a monstrous 1429" roll!  
Ideal for hundreds of applications.*

Blue Monster is a higher-quality PTFE sealing tape that is easier to apply. Blue Monster has not been stretched during the manufacturing process, so it is thicker and creates a more effective seal with less tape, and no need for pipe dope. Use Blue Monster on threads made from galvanized steel, iron, brass, copper, aluminum, stainless steel, polyethylene, polypropylene, PVC, CPVC, ABS, fiberglass and more.



#### Specifications:

**Composition:** 99.6% PTFE < 0.4% Pigment  
**Color:** Blue  
**Thickness:** 0.0035" +/-10% (0.0889 mm +/-10%)

Cat #	Description	Std. Pkg.	Master Pkg.	Wgt./Pkg.
70659	1/4" x 520"	10	100	0.5 lbs.
70660	1/2" x 260"	144	720	5.5 lbs.
70661	1/2" x 520"	144	720	7.5 lbs.
70662	3/4" x 260"	100	500	5.0 lbs.
70663	3/4" x 520"	100	500	7.0 lbs.
70664	1" x 260"	120	600	8.0 lbs.
70665	1" x 520"	120	600	11.0 lbs.
70885	1/2" x 1429"	45	270	5.5 lbs.
70886	3/4" x 1429"	27	162	5.0 lbs.
70887	1" x 1429"	27	162	5.75 lbs.
70888	2" x 1429"	27	162	11.40 lbs.


**Density:** 0.8g/cm<sup>3</sup>

**Elongation:** 100%

**PSI rating:** 10,000 PSI (69,000 kPa) water and oil

**Temperature range:** -450°F to +500°F (-268°C to +260°C) PTFE is completely stable up to +500°F or +260°C. Decomposition is slow up to +750°F or +400°C. Decomposition will occur on contact with naked flames.

**Tensile strength:** 115N/mm<sup>2</sup>



### Blue Monster® Gas Guard PTFE Thread Seal Tape

*Monstrous 1000" roll! Color coded yellow for easy identification by gas companies worldwide.*

Blue Monster Gas Guard PTFE thread sealing tape is designed specifically for gas lines. This is a full or maximum-density thread sealing tape. Blue Monster Gas Guard tape is approved by relevant authorities and used by the gas industry world-wide. It's color-coded yellow so fitters and inspectors can easily recognize it as an approved tape. Ideally suited for natural gas, propane and butane lines. Use on threads of approved gas piping systems. Do not use Blue Monster Gas Guard Thread Seal Tape on oxygen systems.



Cat #	Description	Std. Pkg.	Master Pkg.	Wgt./Pkg.
70826	1/2" x 1000"	30	180	4.0 lbs.
70827	3/4" x 1000"	24	144	5.0 lbs.

#### Specifications:

**Composition:** 99.0% PTFE <1.0% Pigment

**Color:** Yellow

**Thickness:** 0.004" +/-10% (0.102mm +/-10%)

**Density:** 1.5g/cm<sup>3</sup> +/-10%

**Elongation:** >100%

**Temperature range:** -400°F to +500°F (-268°C to +260°C) PTFE is completely stable up to +500°F or +260°C. Decomposition is slow up to 750°F or 400°C. Decomposition will occur on contact with naked flames.

**Tensile strength:** 10-17 N/mm<sup>2</sup>

Certified to comply with the provisions of MilSpec T-27730A, UL-listed, CSA approved



### Blue Monster Silver-Seal PTFE Thread Seal Tape

*Blends with high-end finishes including chrome, stainless steel and nickel for dependable, leak-proof joints..*

Blue Monster® Silver-Seal Tape creates dependable, leak-free joints on plumbing fixtures made with chrome, stainless steel and nickel finishes. The silver color of this professional-grade tape blends with high-end finishes minimizing any exposure. Unsightly thread seal tape previously exposed on high-end fixtures, cheapening their appearance, is a thing of the past. Best of all, contractors can rely upon the sealing quality of Blue Monster Silver-Seal tape; it's thicker and creates a more effective seal with less tape.



Cat #	Description	Std. Pkg.	Master Pkg.	Wgt./Pkg.
70658	1/2" x 520" roll	30	360	3.0 lbs.



**Thickness:** 0.0035" +/-10% (0.0889 mm +/-10%)

**Density:** 0.8g/cm<sup>3</sup>

**Elongation:** 100%

**Tensile strength:** 115N/mm<sup>2</sup>

**PSI rating:** 10,000 PSI (69,000 kPa) water and oil

**Temperature range:** -450°F to +500°F (-268°C to +260°C) PTFE is completely stable up to +500°F or +260°C. Decomposition is slow up to +750°F or +400°C. Decomposition will occur on contact with naked flames.

# Clean-Fit Products



## BLUE MONSTER Products

### Blue Monster Stay-Soft Thread Sealant with PTFE

*Specially formulated for residential and commercial fire sprinkler systems*

Blue Monster Stay-Soft PTFE enriched pipe thread compound does not harden and allows for pre-fab application to threads weeks before system assembly and pressurization. Stay-Soft is non-seizing and allows for easy disassembly of any threaded connection years after assembly. Easy clean-up and indefinite shelf life.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76023	1/4 pint / 4 fl. oz. / 118 ml	24	18 lbs (8.2 kg)
76025	1/2 pint / 8 fl. oz. / 237 ml	24	26 lbs (11.8 kg)
76027	1 pint / 16 fl. oz. / 473 ml	12	25 lbs (11.3 kg)
76029	1 quart / 32 fl. oz. / .95 liter	12	50 lbs (22.7 kg)

Approved for use on all metal threaded connections, FlowGuard Gold®, Blazemaster®, and Corzan® pipe and fittings.

Meets Mil. Spec. TT-S-1732  
 Temperature range: -15°F (-20°C) to +400°F (204°C)  
 Pressure ratings: Gases up to 5,000 PSI (351.5 kg/cm<sup>2</sup>)  
 Liquids up to 10,000 PSI (703.1 kg/cm<sup>2</sup>)



### Blue Monster Industrial Grade Thread Sealant

BLUE MONSTER Industrial Grade Pipe Thread Compound is a slow-drying, soft-setting, non-hardening pipe thread compound. Specially formulated with superb "sticking" characteristics, BLUE MONSTER applies evenly and quickly to threads. Recommended for on-site or assembly line work, BLUE MONSTER is lead-free, non-toxic and will not harden or separate in the can.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76007	2 fl. oz. Squeeze Tube	24	4 lbs.
76009	1/4 pint / 4 fl. oz. / 118 ml	24	15 lbs.
76011	1/2 pint / 8 fl. oz. / 237 ml	24	23 lbs.
76015	1 pint / 16 fl. oz. / 473 ml	12	22 lbs.
76019	1 quart / 32 fl. oz. / .95 liter	12	48 lbs.

Meets Mil. Spec. TT-S-1732  
 Temperature range: -50°F (-45°C) to +400°F (204°C)  
 Pressure ratings: Gases up to 3,000 PSI (211 kg/cm<sup>2</sup>)  
 Liquids up to 6,000 PSI (422 kg/cm<sup>2</sup>)

Not recommended for use on oxygen systems.  
 Use Clean-Fit 3-wrap Oxygen PTFE Tape.



### Blue Monster Industrial Grade Thread Sealant with PTFE

Formulated for extra lubrication on metal pipe threads, BLUE MONSTER Industrial Grade Thread Sealant with PTFE is a slow-drying, soft-setting, non-hardening pipe thread compound. BLUE MONSTER has a high bulk density, which means there are more solids in the formulation. Recommended for on-site or assembly line work. It is lead-free, non-toxic and will not harden or separate in the can.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76000	2 fl. oz. Squeeze Tube	24	4 lbs.
76001	1/4 pint / 4 fl. oz. / 118 ml	24	15 lbs.
76003	1/2 pint / 8 fl. oz. / 237 ml	24	23 lbs.
76005	1 pint / 16 fl. oz. / 473 ml	12	22 lbs.
76017	1 quart / 32 fl. oz. / .95 liter	12	48 lbs.

Meets Mil. Spec. TT-S-1732  
 Temperature range: -50°F (-45°C) to +400°F (204°C)  
 Pressure ratings: Gases up to 3,000 PSI (211 kg/cm<sup>2</sup>)  
 Liquids up to 10,000 PSI (703.1 kg/cm<sup>2</sup>)

Not recommended for use on oxygen systems.  
 Use Clean-Fit 3-wrap Oxygen PTFE Tape.



### Blue Monster® Copper Anti-Seize Lubricant

*Copper anti-seize lubricant for use on all metal pipe and fittings.*

Mill-Rose Blue Monster Copper Anti-Seize is a specially formulated copper-based lubricant for high temperature up to 1800°F (982°C) and high pressure environments. Blue Monster Copper Anti-Seize lubricant will not bleed, separate, or settle. Prevents pressure leakage and seizing resulting from high temperature, freezing, heavy loads, corrosion, and vibration. Contains no grit. Prevents rust and corrosion.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76024	10 oz. / .625 lb. / .283 kg	12	9.4 lbs.
76026	16 oz. / 1.00 lb. / .454 kg	12	15.2 lbs.

- Copper anti-seize lubricant for use on all metal pipe and fittings.
- Temperature Range Use:  
 Gases: -0°F (-17°C) to 1800°F (982°C)  
 Liquids: -0°F (-17°C) to 1800°F (982°C)  
 Brushable to: 10°F (-12°C)  
 Pour Point: 32°F (0°C)





## BLUE MONSTER Products

### Blue Monster® Nickel Anti-Seize Lubricant

Pure nickel anti-seize compound for use on stainless steel pipe and fittings.

Blue Monster Nickel Anti-Seize is an extreme service anti-seize lubricant for use in a high temperature environment (up to 2600°F /1427°C). For use in applications where copper, lead, molybdisulfide, chlorides, and fluorides cannot be tolerated. Blue Monster Nickel Anti-Seize lubricant is chemically inert and can be used with most chemicals that are unstable with copper-type compounds. Provides excellent resistance to chemical oxidation and/or



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76020	8 oz. / .500 lb. / .277 kg	12	10 lbs.
76022	16 oz. / 1.00 lb. / .454 kg	12	19 lbs.

corrosion. Prevents rusting, seizing, welding, or galling. Not for use on potable water systems.

- High temperature lubricant for use on stainless steel, PVC, CPVC, nylon, polypropylene, plastics and all metals.
- Temperature Range Use:  
Gases: -0°F (-17°C) to 2600°F (1427°C)  
Liquids: -0°F (-17°C) to 2600°F (1427°C)  
Brushable to: 10°F (-12°C)      Pour Point: 32°F (0°C)

### Blue Monster® Nickel Guard® Anti-Seize Thread Seal Tape

Easy assembly and disassembly of threaded components

- 10% Nickel Flake Content
- A clean and efficient alternative to anti-seize compounds
- A nickel impregnated PTFE thread sealing tape designed for stainless steel fittings
- Anti-seize assistance up to 2,651°F (1,455°C)



A unique thread sealing tape that prevents stainless steel fittings from galling or seizing during assembly and disassembly. This tape is impregnated with nickel powder which acts like bearing plates, keeping the surface of the male/female threads apart. Further protection is provided with this thicker and denser tape that ensures an effective seal. Nickel Guard® Anti-Seize Thread Sealing Tape is recommended for stainless steel pipe and fittings but it is compatible with a wide range

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70894	1/2" x 600"	10	1.14 lbs.
70895	3/4" x 600"	8	1 lb.

of piping materials for use with a wide range of gases and liquids. Additional features include no curing time, effective across a broad range of temperatures, and it's non-toxic and non-flammable.

#### Specifications:

- Composition:** 90% PTFE / 10% nickel
- Color:** Silver
- Thickness:** 0.0045" +/- 10% (0.115mm +/-10%)
- Density:** 1.6g/cm<sup>3</sup> +/- 10%
- Elongation:** 50%
- Temperature range:** -450°F to +500°F (-268°C to +260°C) PTFE is completely stable up to +500° F or +260° C. Decomposition will occur on contact with naked flames. Upon decomposition, the remaining copper powder will assist disassembly. Nickel flake will melt at 2,651°F or 1,455°C.
- Tensile strength:** 10-12N/mm<sup>2</sup>

### Blue Monster® Copper Guard® Anti-Seize Thread Seal Tape

Easy assembly and disassembly of threaded components

- 10% Copper Flake Content
- A clean and efficient alternative to anti-seize compounds
- A copper impregnated PTFE thread sealing tape
- Anti-seize assistance up to 1,984°F (1,084°C)



Designed to permit the easy assembly and disassembly of threaded components. It takes the place of messy and potentially contaminating anti-seize compounds. Blue Monster® Copper Guard® Anti-Seize Tape is manufactured from a copper filled PTFE resin that provides excellent lubricity and helps prevent galling during assembly and disassembly of components. When wrapped around a thread, Mill-Rose Blue Monster® Copper Guard® Anti-Seize Tape seals it from corrosive substances or any dirt or grit likely to cause seizure. Apply to any threaded component

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70811	1/2" x 600"	10	1.14 lbs.
70812	3/4" x 600"	8	1 lb.

made from galvanized steel, steel, iron, brass, copper, aluminum, titanium and magnesium. It is not recommended for stainless steel.

#### Specifications:

- Composition:** 90% PTFE / 10% copper
- Color:** Copper
- Thickness:** 0.0045" +/- 10% (0.115mm +/-10%)
- Density:** 1.6g/cm<sup>3</sup> +/- 10%
- Elongation:** 50%
- Temperature range:** -450°F to +500°F (-268°C to +260°C) PTFE is completely stable up to +500° F or +260° C. Decomposition will occur on contact with naked flames. Upon decomposition, the remaining copper powder will assist disassembly. Copper flake will melt at 1,984°F or 1,084°C.
- Tensile strength:** 10-12N/mm<sup>2</sup>

# Clean-Fit Products



## BLUE MONSTER Products

### Blue Monster Six-in-One Brush

Blue Monster Six-in-One Brush cleans the inside diameter of 1/2" and 3/4" fittings and outside diameter of 1/2" and 3/4" tubing. The deburring plate reams and deburs the I.D. of tubing, has a b-tank gas key (square opening on plate), and also serves as a bottle opener.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
70255	1/2" x 3/4" ID Brush/Deburrer	10	3.50 lbs.
70269	1/2" x 3/4" Replacement Kit	6	.60 lbs.
70271	Adapter Kit (Deburring plate)	6	.50 lbs.

### Blue Monster Contractor Grade Abrasives

2" Width – 33% wider than traditional plumbers' rolls and 100% waterproof.

Blue Monster premium open mesh and Ultra-Flex® abrasive cloth are revolutionary, high-performance abrasives that are tough! Blue Monster outlasts all others in the most demanding conditions, wet or dry. Blue Monster's wide design provides more surface-to-surface coverage making it easier and faster to prep large-diameter tube and fittings.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
<b>Blue Monster Open Mesh</b>			
70151	2" x 8" mini strips (10)	12	1.85 lbs.
70152	2" x 5 yard roll	12	6.20 lbs.
70154	2" x 10 yard roll	12	10.50 lbs.
70156	2" x 25 yard roll	12	22.00 lbs.
<b>Blue Monster Ultra-Flex</b>			
70171	2" x 8" mini strips (10)	12	1.85 lbs.
70172	2" x 5 yard roll	12	5.00 lbs.
70174	2" x 10 yard roll	12	8.75 lbs.
70176	2" x 25 yard roll	12	20.00 lbs.

*Premium*



**Aluminum Oxide  
Open Mesh  
Abrasive**

- 21 x 21 Mesh – Has larger holes than other open mesh products. This feature prevents "loading" and allows contractors to rinse the mesh clean. Resists clogging even when used on softer materials.
- Premium blended 165 grit white Aluminum Oxide cuts and scores surfaces faster for more effective cleaning and deburring.

*Premium*



**Ultra-Flex®  
Abrasive  
Cloth**

- Super flexible Ultra-Flex® backing conforms to tight work areas and Blue Monster will not crack or tear during use.
- Premium 150 grit cuts and scores surfaces faster for more effective cleaning and deburring.

### Arctic Armor Thermal Shield Gel

Blue Monster Arctic Armor creates a thermal barrier that protects surfaces from heat damage during soldering, welding and brazing operations. Spray on hard-to-reach surfaces or apply to any surface to shield studs, walls, floors and other surfaces from flames, sparks and molten splash. Arctic Armor's unique, no-drip gelled formula evaporates within 48 hours, eliminating cleanup.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
71028	Arctic Armor Thermal Shield Gel	12	48.0 lbs.

- Protects valve seals and seats from heat damage during soldering
- Protects soldered joints from loosening when soldering new joints.
- Protects wood, metal, plastic, rubber, wire, insulation, drywall, painted surfaces and more.
- Unique gelled formula sticks to surfaces without dripping or running
- Safe, non-toxic, harmless to skin, and odorless





## BLUE MONSTER Products

### Blue Monster Torch Guard Heat Shield

Shield studs, walls, floors and surfaces from flames, sparks and molten splash during soldering and brazing operations

Professional contractors and do-it-yourselfers appreciate the flame resistance and liability protection provided by Blue Monster Torch-Guard. It's asbestos-free (OSHA's Material Safety Data Sheet on Torch-Guard is available) and features high-strength needle-punched carbon fiber that stands up to heat while other materials peel, flake and break down. Ideal for confined working areas, Blue Monster Torch-Guard is very flexible, easy to work with and provides heat resistance up to, but not exceeding 2500°F. This heat shield has two grommets for hanging, is flexible and will not peel, flake or break down.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
71032	9" x 12" Torch Guard Shield	5	1.1 lbs.
71034	12" x 12" Torch Guard Shield	5	1.5 lbs.

- Protects against flames and sparks during soldering and brazing
- Ideal for higher-temperature torches
- Flame resistance to 2,500°F



Attractive display for shelves and counters grabs contractor's attention.

### Blue Monster Power Deuce Brushing Tool Two Brushes in One!

Multi-function brush cleans fittings and tubing for stronger joints.

The Power-Deuce is a multi-function brushing tool that prepares the inside of copper fittings and outside of copper tubing without having to change tools. The Power-Deuce is a self-cleaning brush with rust-proof, stainless steel bristles for plumbing and HVAC projects. A heavy-duty ABS housing is impact resistant and protects bristles so they retain their shape and prolongs brush life.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
<b>12-Pack Counter/Shelf Display</b>			
62820	1/2 I.D. (5/8" O.D.)	12	2.0 lbs.
62830	3/4" I.D. (7/8" O.D.)	12	2.4 lbs.
62840	1" I.D. (1-1/8" O.D.)	12	3.0 lbs.
<b>Power Pack with Quik Change Chuck Adapter</b>			
62850	1/2 I.D. (5/8" O.D.) 3/4" I.D. (7/8" O.D.) 1" I.D. (1-1/8" O.D.)	6	1.2 lbs.
<b>Individually Packaged on Blister Card</b>			
62821	1/2 I.D. (5/8" O.D.)	12	2.0 lbs.
62831	3/4" I.D. (7/8" O.D.)	12	2.4 lbs.
62841	1" I.D. (1-1/8" O.D.)	12	3.0 lbs.



Blue Monster Power-Deuce Power Pack contains three popular sizes of Power-Deuce brushes plus a Quik-Change chuck adaptor.

### Blue Monster Heavy-Duty, Professional PLUMBING/REFRIGERATION Brushes

Blue Monster heavy-duty plumbing and refrigeration brushes set the industry's standard for quality. Features include heavy-gauge galvanized stem wire and double stem, double-spiral construction for long-lasting performance. The 6300 Heavy-Duty Plumbing brush features oil-tempered straight high-carbon fill wire. The 6400 Heavy-Duty Refrigeration brush features rust proof, spring-tempered straight stainless steel fill wire.



Carbon Steel Plumbing	(I.D.)	Stainless Steel Refrig.	(O.D.)	Std. Pkg.	Wgt./Pkg.
63005	1/8"	64005	1/4"	1	.13 lbs.
63015	1/4"	64020	3/8"	1	.13 lbs.
63025	3/8"	64030	1/2"	1	.18 lbs.
63035	1/2"	64040	5/8"	1	.18 lbs.
63050	5/8"	64050	3/4"	1	.18 lbs.
63060	3/4"	64060	7/8"	1	.18 lbs.
63075	7/8"	64070	1"	1	.18 lbs.
63085	1"	64080	1-1/8"	1	.25 lbs.
63095	1-1/4"	64090	1-1/4"	1	.25 lbs.
63105	1-1/2"	64100	1-3/8"	1	.25 lbs.
63115	2"	64115	1-1/2"	1	.25 lbs.
		64125	1-5/8"	1	.25 lbs.
		64135	2-1/8"	1	.25 lbs.
		64145	2-1/2"	1	.25 lbs.

## BLUE MONSTER Products

### Blue Monster® Microbubble Gas Leak Detector

*Detects even the smallest of leaks*

Blue Monster® Microbubble leak detector is a sensitive solution formulated to detect even the smallest of leaks in air and gas lines, tanks, cylinders, valves, fittings, pipelines, and other suspect areas. Blue Monster's dependable formula provides long lasting leak detection up to 10 minutes after application. Ideal for identifying leaks in refrigeration and air conditioning systems, this easy-to-use leak detector is equally effective on natural gas, propane, butane, air, nitrogen, chlorine, CO2, and most other gases. Not for use on oxygen systems.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
71023	1/2 pint / 8 fl. oz. / 236 ml	24	16 lbs.
71025	1 pint / 16 fl. oz. / 473 ml	12	15 lbs.
71027	1 quart / 32 fl. oz. / 936 ml	12	31 lbs.
71029	1 gallon / 3.75 liters	4	37 lbs.

- Non-freezing formula usable from -10°F (-23°C) to 215°F (101°C).
- Will not cause corrosion or deterioration of metal or plastic piping systems.
- Ideal for testing pressure less than 1psi.

### Blue Monster 1-Step Weatherproof PVC Cement Blue and Clear Formulas

*Self-priming PVC glue simplifies installations*



1-Step Blue PVC Cement

Blue Monster 1-Step PVC cement is a self-priming PVC pipe glue that requires no additional primer. Blue Monster's 1-step joining process simplifies installations by reducing labor and offers faster curing times before pressure testing. Ideal for under-the-sink jobs and home remodels. Use on all classes of rigid and flexible PVC pressure pipe, including Sch. 80, up to 6" in diameter and 8" diameter on nonpressure rigid and flexible PVC pipe.

#### Medium Body - Low VOC

Blue Monster 1-Step PVC cement emits less than 510 grams per liter VOC when tested according to SCAQMD method 316 A.

\*Use without primer where acceptable by local code.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
<b>Blue PVC Cement</b>			
76030	1/4 pint / 4 fl. oz. / 118 ml	24	10 lbs.
76032	1/2 pint / 8 fl. oz. / 237 ml	24	16 lbs.
76034	1 pint / 16 fl. oz. / 473 ml	12	15 lbs.
76036	1 quart / 32 fl. oz. / .95 liter	12	28 lbs.
<b>Clear PVC Cement</b>			
76031	1/4 pint / 4 fl. oz. / 118 ml	24	10 lbs.
76033	1/2 pint / 8 fl. oz. / 237 ml	24	16 lbs.
76035	1 pint / 16 fl. oz. / 473 ml	12	15 lbs.
76037	1 quart / 32 fl. oz. / .95 liter	12	28 lbs.



1-Step Clear PVC Cement



pw/dwv/sw  
Standard 14  
Standard 61



m  
R

# MILL-ROSE

## BLUE MONSTER Products

### Blue Monster® Compression Seal Tape

*Stops problem leaks under pressure without turning off the water source!*

Blue Monster® Compression Seal Tape features self-fusing layers that form a waterproof compression seal. Seal leaks while under pressure - up to 150 PSI on any type of rigid piping material, from galvanized and cast iron to copper and all types of plastics and rubber.

Blue Monster Compression Seal Tape contains no adhesive and is ideal for crisis and long-term applications. This tape seals by compression, so pulling the tape as tight as possible forms a chemical reaction that fuses the layers of tape into a mass of silicone.



Cat #	Description	Std. Pkg.	Master Pkg.	Wgt./Pkg.
76084	1" x 12" Strip Pack (3 Strips)	20	40	3.5 lbs.
76085	1" x 12-foot Rolls	10	40	3.5 lbs.
76086	2" x 12-foot Rolls	6	24	4.0 lbs.

### Specifications:

<b>Thickness:</b>	0.045"
<b>Tear Resistance:</b>	~ 12 lbf/in
<b>UV Resistance:</b>	Highly UV resistant
<b>Elongation:</b>	>325%
<b>Adhesion(Fusion):</b>	Standard requirement: "Tape shall not unwind more than 1.0 inch after 3 minutes with an attached load of 600g. Result: <1 inch
<b>Temperature range:</b>	-90°C to +260°C / -130°F to 500°F
<b>Thermal Stability:</b>	-900°C to +260°C / -130° to 500°F continuous



<b>Tensile strength:</b>	~ 1200 PSI throughout temperature range
<b>Acid/Alkaline/Chlorine:</b>	No negative effect from brief exposure to acids, alkaline or chlorine and can withstand submersion up to 3 days.
<b>Self-Extinguishing:</b>	UL standard 94 rating V-0. Tested to IEEE 383 and IEEE 1202 for flammability, self-extinguishes and will not propagate a flame.

### Standards Compliance:

ASTM D2240, D2240, A-A-59163, ASTM D-149, MIL-I-46852, ASTM D2148, ASTM D3767 Blue Monster Compression Seal Tape specifications meet other international standards not included in this list.



### Blue Monster Heavy-Duty Citrus Scrubbing Towels

*Clean hands, tools, equipment, and hard surface areas with these convenient scrubbing towels.*

BLUE MONSTER scrubbing towels are pre-moistened, heavy-duty cleaning towels dispensed from a handy, flip-top container. They are saturated with a safe, effective cleaning solution combined with a tough, dual-textured towel to loosen, dissolve and absorb dirt and grease leaving your hands clean. One side is rough for scrubbing and the other side is smooth. These towels require no water and leave hands feeling conditioned and clean with no left-over residue.



Free Hand & Nail Brush included in each container!

Cat #	Description	Std. Pkg.	Master Pkg.	Wgt./Pkg.
77095	75 10" x 12" Towels	20	320	57 lbs.

Keep hands, tools and hard surfaces clean from...

- Adhesives
- Flux
- Oils & Inks
- Tar
- Pipe Cements
- Asphalt
- Grease
- Paint
- Lubricants
- Urethanes & More
- Heavy Soil
- Grime
- Pipe Dope
- Caulk



Attractive floor display grabs consumer's attention.



# Clean-Fit Products




## BLUE MONSTER Products

Our bolt's patented broach-tip design gives the installer the direction of the foot underneath the flange. Each kit includes 2 solid brass bolts, 2 solid brass hex nuts, 2 solid brass open-ended acorn hex nuts, 4 stainless steel washers and 2 nylon tinnerman nuts. Not only does our bolt provide foot direction but also provides a true hold-back and break-off eliminating the need for a hacksaw.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
73065	5/16" x 2-1/4"	100	16 lbs.
73070	5/16" x 3-1/2"	100	22 lbs.
73064	1/4" x 2-1/4"	100	10 lbs.
73069	1/4" x 3-1/2"	100	16 lbs.



*Raised knobs on underside prevents movement after installation.*



### Blue Monster® Drain Banger

*Professional strength, odorless drain opener*

Blue Monster Drain Banger devours hair, grease, soap and oils that slow and plug drain lines in less than 60 seconds! Blue Monster Drain Banger is a hot water activated non-acid drain cleaner designed to be used by professional contractors only. It is odorless and will not harm plumbing fixtures, porcelain or septic systems.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76055	1 lb. (453 g)	24	26 lbs.
76057	2 lbs. (907 g)	12	26 lbs.
76059	6 lbs. (2722 g)	4	24 lbs.

- Devours hair, grease, soap, oils and other organic materials that slow and plug drain lines in less than 60 seconds!
- For professional contractors only!
- Non-Acid
- Odorless



# MILL ROSE

## Point-of-Sale Gondola Display Program



**48"**

### ***Gondola Displays***



**24"**



**36"**





# Clean-Fit Products

m  
R

## Monster Notes

# BLUE MONSTER<sup>®</sup>

Products



**MILL-ROSE** *Clean-Fit Products*

The Mill-Rose Company  
Clean-Fit Products  
7310 Corporate Blvd.  
Mentor, OH 44060 U.S.A.

T: 800.321.3598  
Fax: 440.255.1072  
info@cleanfit.com  
cleanfit.com